





ORDER TODAY OR FOR MORE INFORMATION:

Visit our website to download support material or contact one of our helpful Sales Representatives.

www.textor.com.au

Textor Metal Industries Pty Ltd

14–20 Magnesium Drive, Crestmead Industrial Estate Crestmead, Queensland Australia, 4132

P 07 3803 6377

F 07 3803 6352

E info@textor.com.au

Notes:

For customisation of Textor products please contact one of our knowledgeable staff.

Please be aware of local building requirements. If this product will be used in exposed situations within 1km of salt marine locations, or in severe industrial or unusually corrosive environments, alternative coating type may be required.

Light and strong with a smooth 'no bruise' profile, the Textor Stockyard rail is designed with animal safety in mind. Our rolled back edges improve living conditions while minimising the risk of entrapment injuries to your valuable stock. Textor Stockyard Rail is ideal for fences, gates and yards. Suitable for a range of rural applications, it can be rolled cut to your desired length (for quantity orders), eliminating wastage and providing an even greater saving.

Features

- Available in 7", 9" and 11" widths in both black and lasting galvanised finishes (lasting rust protection)
- Wide profile making it a good visual barrier to stock and horses
- Large range of standard sizes and thicknesses
- Customisations available to meet your specific needs

Finishes:

- Galvanised Steel
- Black

Customisations:

- Cut to length
- Grade and gauge
- Coating thickness on galvanised finish
- Custom roll form and modified profiles

Availability:

- Standard sizes on site ready for dispatch
- Textor Product Specifications Brochure
- Customisations with minimum delay

Support Material Available:

- CAD Drawings
- Product Specifications

Example Applications:

- Farming (feed lot yards, stockyard fences, gates and horse spelling yards)
- Also popular as panelling under houses and security panelling



STOCKYARD RAIL



1. Stockvard Rail

| PROFILE CODE | PROFILE DESCRIPTION | D (MM) | B (MM) | L (MM) | GAUGE (MM) | SECTION | KG PER M | MATERIAL | SPECIAL |
|--------------|---------------------------------|--------|--------|--------|------------|------------|----------|-------------|---------|
| | | | | | | AREA (MM²) | | DESCRIPTION | NOTE |
| TSR18512B | BLACK 185X19X1.2 STOCKYARD RAIL | 185 | 19 | 47 | 1.2 | 272.4 | 2.13834 | BLACK | * |
| TSR18516B | BLACK 185X19X1.6 STOCKYARD RAIL | 185 | 19 | 47 | 1.6 | 363.2 | 2.85112 | BLACK | |
| TSR18516G | GALV 185X19X1.6 STOCKYARD RAIL | 185 | 19 | 47 | 1.6 | 363.2 | 2.91695 | GALV | |
| TSR18520B | BLACK 185X19X2.0 STOCKYARD RAIL | 185 | 19 | 47 | 2 | 450 | 3.5325 | BLACK | |
| TSR18520G | GALV 185X19X2.0 STOCKYARD RAIL | 185 | 19 | 47 | 2 | 450 | 3.59775 | GALV | |
| TSR23510G | GALV 235X19X1.0 STOCKYARD RAIL | 235 | 19 | 47 | 1 | 280 | 2.2792 | GALV | |
| TSR23512B | BLACK 235X19X1.2 STOCKYARD RAIL | 235 | 19 | 47 | 1.2 | 332.4 | 2.60934 | BLACK | * |
| TSR23516B | BLACK 235X19X1.6 STOCKYARD RAIL | 235 | 19 | 47 | 1.6 | 443.2 | 3.47912 | BLACK | |
| TSR23516G | GALV 235X19X1.6 STOCKYARD RAIL | 235 | 19 | 47 | 1.6 | 443.2 | 3.55945 | GALV | |
| TSR23520B | BLACK 235X19X2.0 STOCKYARD RAIL | 235 | 19 | 47 | 2 | 550 | 4.3175 | BLACK | |
| TSR23520G | GALV 235X19X2.0 STOCKYARD RAIL | 235 | 19 | 47 | 2 | 550 | 4.39725 | GALV | |
| TSR28012B | BLACK 280X19X1.2 STOCKYARD RAIL | 280 | 19 | 47 | 1.2 | 381.6 | 2.99556 | BLACK | * |
| TSR28016B | BLACK 280X19X1.6 STOCKYARD RAIL | 280 | 19 | 47 | 1.6 | 507.2 | 3.98152 | BLACK | |
| TSR28016G | GALV 280X19X1.6 STOCKYARD RAIL | 280 | 19 | 47 | 1.6 | 507.2 | 4.07345 | GALV | |

^{*} SUBJECT TO MINIMUM ORDER REQUIREMENTS IF NOT IN STOCK